

SILVER

AKOS

HIGH SPEED
HANDPIECE

1

SILVER



Order NO:
A02-SPM2

Parameter

Material	Titanium
Noise	≤68dB
Size of the Head	11.25 * 13.3mm
Maximum speed	360000-380000rpm
Bearing	Ceramic Ball Bearing
Spray	single port water spray

نهایت دمای مناسب اتوکلاو ۱۳۵°C می باشد.

HIGH SPEED HANDPIECE

2

SILVER



Order NO:
A04-SP M2



Order NO:
A04-SP M4

Parameter

	A 04 - SP M2	A 04 - SP M4
Head Diameter	11.25 x 13.3 mm	11.25 x 13.3 mm
Noise	≤68dB	
Material	Coper	
Maximum speed	350,000-380,000rpm	
Bearing	Ceramic Ball Bearing	
Spray	4-port water spray	

نهایت دمای مناسب اتوکلاو ۱۳۵°C می باشد

MINI HEAD HANDPIECE FOR CHILDREN

3

SILVER



- Small, Quiet
- Slender head, born to Children
- Long Service life
- Open cartridge, ease of maintenance



Order NO:
A04 - MP

Parameter

Head Diameter (W*H)	10.6*8.6
Noise	≤68dB
Material	Coper
Maximum speed	350000-380000rpm
Bearing	NSK Ceramic Ball Bearing
Spray	4-port water spray

نهایت دمای مناسب اتوکلاو ۱۳۵°C می باشد

Low Speed
Contra Angle

4

SILVER

Rotary Head



Implant Head



Parameter

	Angle Rotary K32	Implant k26
Material	Copper	Titanium
Working dB	≤63dB	≤63dB
Bearing	Ceramic Ball Bearing	NSK Ceramic Ball Bearing
Max Torque	2,000RPM	2,000RPM
Bur Type	CA Bur (2.35mm)	CA Bur (2.35mm)
Spray	External	External
Gear Ratio	64:1	20:1

نهایت دمای مناسب اتو کلاو ۱۳۵°C می باشد

INNER WATER
LOW SPEED HANDPIECE SERVICE

5

SILVER

Model K21 - AM



2 hole

Whole body
stainless steel and imported
EZO bearing

Air Motor
K21-AM

Parameter

Maximum speed	2,000RPM
Air pressure	2.8~3.0Kpa
Forward	1.8000r/min≤
Reverse	≥1.7000r/min

نهایت دمای مناسب اتو کلاو ۱۳۵°C می باشد



External Straight Head
LOW SPEED HANDPIECE SERVICE

6

SILVER



Material
Stainless Steel

Straight Handpiece
K-21-SH

Parameter

External Straight Head	K21-SH
Gear Ratio	1-1
Max Speed	40,000rpm
Bur applicable	2.35mm

نهایت دمای مناسب اتوکلاو ۱۳۵ °C می باشد

Low Speed
Reciprocating 10.1

7

SILVER



Order NO:
K 29-CA

Parameter

Endolif 10.1	K29-CA
Working temperature	≤20°C
Maximum speed	10,000RPM
Noise	≤58dB
Bearing	Ceramic Ball Bearing

نهایت دمای مناسب اتوکلاو ۱۳۵ °C می باشد



LOW SPEED
CONTRA ANGLE

8

SILVER



Push type
Angle

K21-CA-P



LatchType
Angle

K21-CA

TECHNICAL PARAMETER

Gear Ratio	1:1
Working	≤63dB
Materials	Copper
Max Speed	2,000rpm
Air consumption	56NL/min
Bur Type	ø2.35mm
Air pressure	2.8~3.0Kpa
Type of chuck	Push button

External Contra Angle

Gear Ratio	1:1
Spray	External
Working	63dB ≥
Max speed	2000rpm
High temperature	135°C
Type of Chuck	Latch type

نهايت دمای مناسب اتوکلاو ۱۳۵ °C می باشد

